

comp.150 Combined Optical Matrix Punch

General Data

Width:	720mm
Depth:	600mm
Height:	1100mm
Weight:	approx. 500kg

Electrical Supply

Power supply:
110V±10%/3Ph/N/PE/50/60Hz
220V±10%/3Ph/N/PE/50/60Hz

Power consumption: 350 W

Punch & Die Set

Inner diameter:
up to 38mm , tolerance ±0.005mm

Outer diameter:
Up to 150mm, tolerance ± 0.004mm

Concentricity to information: 0.005mm

MEDIA SERVICES GROUP

10 Iron Trail Rd.
Biddeford, ME 04005
USA
Phone: 207-286-3000
Fax: 207-286-2338
info@mediaservicesgroupusa.com



The comp.150 has been designed to consistently achieve accurate high volume stamper centring and punching. Inner and outer diameter are punched in one process.

Continued punching quality and reliability is guaranteed by robust construction and simple operation, resulting in excellent punch hole roundness. The self aligning facility allows rapid exchange of punch and die assembly. The ID punch and die can be changed independently to accommodate different centre hole size.

Safety interlocks protect both operator and equipment during use and contribute to the comp.150 conforming to international safety standards. The compact comp.150 can be mounted on a purpose-built bench.