

trimmer

Optical Disc Stamper Edge Cutter

General Data

Width:	465mm
Depth:	620mm
Height:	345mm
Weight:	approx. 50kg

Electrical Supply

Power supply:
AC 100 - 230V \pm 10%/50 - 60Hz

Power consumption: 170 W

Diameters

Trim diameter range: 145mm - 265mm
Trim diameter accuracy: \pm 0.5mm
Repeatability: \pm 0.05mm

Optional

Selectable preset trimming diameters
Purpose built bench

MEDIA SERVICES GROUP

10 Iron Trail Rd.
Biddeford, ME 04005
USA
Phone: 207-286-3000
Fax: 207-286-2338
info@mediaservicesgroupusa.com



The Trimmer has been specifically designed to fully automate the edge cutting process for the outside diameter of fathers and mothers. It has a large range diameter adjustment, that can be set to suit any size of mounting plate.

The trim diameter adjustment and wand data alignment system is very simple and quick to use, which makes the Trimmer ideal for production, archive mothers, R&D and experimental work. The trim diameter range is 145mm to 265mm, with a cycle time of two minutes.

The cutting wheels are TIN coated and trimming diameters can be preset. The compact pneumatically operated Trimmer is bench mountable and built to exacting standards to ensure accuracy and reliability.